



MSDS

Report No.: PTC19081602503C-EN01

Issue Date: Nov. 05, 2019

Page 1 of 8

Applicant : Acumentrics, Inc.
Address : 10 Walpole Park South Walpole, MA 02081 USA
Sample Name : Lithium-ion Rechargeable Battery
Model No. : IM1146
Product Specification : 11.1V 9Ah
Manufacturer : ICON ENERGY SYSTEM (SHEN ZHEN) CO., LTD
Address : No.4, guanqing road, luhu community, guanhu street, longhua district, shenzhen
Sample Received Date : Sep. 17, 2019
Completed Date : Sep. 23, 2019



Signed for and on Behalf of PTC

Frank Lin / Laboratory manager
DongGuan Precise Testing and Certification Corp. Ltd.

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.
The report could not be copied without permission

DongGuan Precise Testing and Certification Corp. Ltd. (PTC)
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.
Tel: 86-769-38808222 Fax: 86-769-38826111 [http:// www.ptc-testing.com](http://www.ptc-testing.com)



MSDS

Report No.: PTC19081602503C-EN01

Issue Date: Nov. 05, 2019

Page 2 of 8

Material Safety Data Sheet

Section 1 - Chemical Product and Company Identification

Product Identification

| | |
|---------------------|--|
| Product Name | Lithium-ion Rechargeable Battery |
| Model No. | IM1146 |
| Applicant | Power System Electronic Technology Co., Ltd. |
| Address | No.1 Shangbian Road, Puxin Industrial District, Shipai Town, Dongguan City, Guangdong, China |
| Manufacturer | ICON ENERGY SYSTEM (SHEN ZHEN) CO., LTD |
| Address | No.4, guanqing road, luhu community, guanhu street, longhua district, shenzhen |

Section 2 - Composition/Information on Ingredients

| Chemical Composition | CAS NO. | Weight(%) |
|--|----------------|------------------|
| Aluminum Foil | 7429-90-5 | 2-10 |
| Nickel compound(proprietary) | 12688-64-1 | 0-25 |
| Manganese compound(proprietary) | -- | 0-15 |
| Cobalt compound(proprietary) | -- | 4-50 |
| Styrene-Butadiene-Rubber | -- | <1 |
| Polyvinylidene Fluoride(PVDF) | 24937-79-9 | <5 |
| Copper Foil | 7440-50-8 | 2-10 |
| Carbon(proprietary) | 7440-44-0 | 10-30 |
| Electrolyte(proprietary) | -- | 10-20 |
| Stainless steel,Nickel and inert materials | -- | -- |

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission

DongGuan Precise Testing and Certification Corp. Ltd. (PTC)

Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.
Tel: 86-769-38808222 Fax: 86-769-38826111 [http:// www.ptc-testing.com](http://www.ptc-testing.com)



MSDS

Report No.: PTC19081602503C-EN01

Issue Date: Nov. 05, 2019

Page 3 of 8

Section 3 –Hazards Summarizing

Battery can explode or leak if heated, disassembled, shorted, recharged, exposed to fire or high temperature or inserted incorrectly. Keep in original package until ready to use. Do not carry batteries loose in your pocket or purse. Keep batteries away from children. If swallowed, consult a physician at once. For information on treatment, call the NATIONAL BUTTON BATTERY INGESTION HOTLINE, collect to the United States of America, day or night, at (202) 625-3333. Under certain misuse conditions and by abusively opening the battery, exposed lithium can react with water or moisture in the air causing potential thermal burns or fire. And also complies with the Special Provision 188 of IMDG CODE (Amdt.39-18) 2019 Edition.

Section 4 - First-aid Measures

| | |
|-----------------------|--|
| General Advice | The chemicals and metals in this product are contained in a sealed can. Exposure to the contents will not occur unless the battery leaks, is exposed to high temperatures or is mechanically, physically, or electrically abused. |
| Eyes | If battery is leaking and material contacts the eye, flush thoroughly with copious amounts of running water for 30 minutes. Seek immediate medical advice. |
| Skin | If battery is leaking and material contacts the skin, remove any contaminated clothing and flush exposed skin with copious amounts of running water for at least 15 minutes. If irritation, injury or pain persists, seek medical advice. |
| Inhaled | If battery is leaking, contents may be irritating to respiratory passages. Move to fresh air. If irritation persists, seek medical advice. |
| Swallowed | If battery is swallowed seek immediate medical advice. Batteries lodged in the esophagus should be removed immediately since leakage, caustic burns and perforation can occur as soon as two hours after ingestion. If mouth area irritation or burning has occurred, rinse the mouth and surrounding area with tepid water for at least 15 minutes. Do not give ipecac. |

Section 5 - Fire Fighting Measures

| | |
|---|--|
| Fire and Explosion Hazards | Batteries may burst and release hazardous decomposition products when exposed to a fire situation. |
| Extinguishing Media | Use any extinguishing media that is appropriate for the surrounding fire. |
| Special Fire Fighting Procedures | Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing. Fight fire from a distance or protected area. Cool fire exposed batteries to prevent rupture. Use caution when handling fire-exposed containers (batteries may explode in heat of fire). |
| Hazardous Combustion Products | Thermal degradation may produce hazardous fumes of lithium and manganese; hydrofluoric acid, oxides of carbon and sulfur and other toxic by-products. |

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission

DongGuan Precise Testing and Certification Corp. Ltd. (PTC)

Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.
Tel: 86-769-38808222 Fax: 86-769-38826111 [http:// www.ptc-testing.com](http://www.ptc-testing.com)



MSDS

Report No.: PTC19081602503C-EN01

Issue Date: Nov. 05, 2019

Page 4 of 8

Section 6 - Accidental Release Measures

Notify safety personnel of large spills. Irritating vapors and flammable may be released from leaking or ruptured batteries. Eliminate all ignition sources. Evacuate the area and allow the vapors to dissipate. Clean-up personnel should wear appropriate protective clothing to avoid eye and skin contact and inhalation of vapors or fumes. Increase ventilation. Carefully collect batteries and place in an appropriate container for disposal. Remove spilled liquid with absorbent and contain for disposal.

Section 7 –Handling And Storage

| | |
|-----------------|--|
| Handling | Avoid mechanical or electrical abuse. DO NOT short circuit or install incorrectly. Batteries may explode, pyrolize or vent if disassembled, crushed, recharged or exposed to high temperatures. Install batteries in accordance with equipment instructions. Replace all batteries in equipment at the same time. Do not carry batteries loose in a pocket or bag. |
| Storage | Store batteries in a dry place at normal room temperature. |

Section 8 - Exposure Controls/Personal Protection

| | |
|---|---|
| Respiratory Protection | In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting cell cores. Respiratory Protection is not necessary under conditions of normal use. |
| Ventilation | Not necessary under conditions of normal use. |
| Other Protective Clothing or Equipment | Not necessary under conditions of normal use. |
| Personal Protection is recommended for venting battery | Respiratory Protection, Protective Gloves, Protective Clothing and safety glass with side shields. |

Section 9 - Physical and Chemical Properties

| | |
|-------------------|--------------|
| Appearance | Square |
| Odour | Odorlessness |
| Colour | Black |

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission

DongGuan Precise Testing and Certification Corp. Ltd. (PTC)
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.
Tel: 86-769-38808222 Fax: 86-769-38826111 [http:// www.ptc-testing.com](http://www.ptc-testing.com)



MSDS

Report No.: PTC19081602503C-EN01

Issue Date: Nov. 05, 2019

Page 5 of 8

| | |
|---------------------------|----------------|
| pH | Not applicable |
| Flash Point | Not applicable |
| Flammability | Not applicable |
| Relative density | Not applicable |
| Solubility (water) | Not applicable |
| Solubility (other) | Not applicable |

Section 10 - Stability and Reactivity

| | |
|--|---|
| Stability | This product is stable. |
| Incompatibility/Conditions to Avoid | Contents are incompatible with strong oxidizing agents. Do not heat, crush, disassemble, short circuit or recharge. |
| Hazardous Decomposition Products | Thermal decomposition may produce hazardous fumes of lithium and manganese; hydrofluoric acid, oxides of carbon and sulfur and other toxic by-products. |
| Hazardous Polymerization | Will not occur |

Section 11 - Toxicological Information

| | |
|---------------------------------|--|
| Potential Health Effects | The chemicals and metals in this product are contained in a sealed can. Exposure to the contents will not occur unless the battery leaks, is exposed to high temperatures or is mechanically, physically, or electrically abused. |
| Eye Contact | Contact with battery contents may cause irritation. |
| Skin Contact | Contact with battery contents may cause irritation. |
| Inhalation | Inhalation of vapors or fumes released due to heat or a large number of leaking batteries may cause respiratory and eye irritation. |
| Ingestion | Swallowing is not anticipated for larger batteries due to battery size. Smaller batteries may be swallowed. If battery is swallowed, seek immediate medical advice. Batteries lodged in the esophagus should be removed immediately since leakage, caustic burns and perforation can occur as soon as two hours after ingestion. Irritation to the internal/external mouth areas, may occur following exposure to a leaking battery. |

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.
The report could not be copied without permission

DongGuan Precise Testing and Certification Corp. Ltd. (PTC)
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.
Tel: 86-769-38808222 Fax: 86-769-38826111 [http:// www.ptc-testing.com](http://www.ptc-testing.com)



MSDS

Report No.: PTC19081602503C-EN01

Issue Date: Nov. 05, 2019

Page 6 of 8

| | |
|------------------------|---|
| Chronic Effects | The chemicals in this product are contained in a sealed can and exposure does not occur during normal handling and use. No chronic effects would be expected from handling a leaking battery. |
| Target Organs | Skin, eyes and respiratory system. |
| Carcinogenicity | None of the components of this product are listed as carcinogens by the EU Directive on the classification and labeling of substances. |

Section 12 - Ecological Information

No ecotoxicity data is available. This product is not expected to present an environmental hazard.

Section 13 - Disposal

Do not incinerate or subject cells to temperature in excess of 80°C. Dispose of in accordance with local regulations.

Section 14 - Transport Information

All lithium, lithium ion and lithium polymer cells and batteries must be tested in accordance with the "UN Manual of Tests and Criteria, Part III, Subsection 38.3 2017.

The 60th edition of the IATA Dangerous Goods Regulations incorporates all amendments made by the ICAO Dangerous Goods Panel in developing the content of the 2019-2020 edition of the ICAO Technical Instructions as well as changes adopted by the IATA Dangerous Goods Board. The following list is intended to assist the user to identify the main changes introduced in this edition and must not be considered an exhaustive listing. The changes have been prefaced by the section or subsection in which the change occurs.

UN3480, PACKING INSTRUCTION 965, Lithium Ion Batteries

UN3481, PACKING INSTRUCTION 966, Lithium Ion Batteries packed with equipment

UN3481, PACKING INSTRUCTION 967 Lithium Ion Batteries contained in equipment

Cells and batteries must be packed in inner packaging that completely encloses the cell or battery.

Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit.

Each consignment must be accompanied with a document such as an air waybill with an indication that:

- the package contains lithium ion cells or batteries;
- the package must be handled with care, and that a flammability hazard exists if the package is damaged;

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission

DongGuan Precise Testing and Certification Corp. Ltd. (PTC)

Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.
Tel: 86-769-38808222 Fax: 86-769-38826111 [http:// www.ptc-testing.com](http://www.ptc-testing.com)



MSDS

Report No.: PTC19081602503C-EN01

Issue Date: Nov. 05, 2019

Page 7 of 8

- special procedures should be followed in the event the package is damaged, to include inspection and repacking if necessary; and
- a telephone number for additional information.

Each package must be labelled with a lithium battery handling label;

Any person preparing or offering cells or batteries for transport must receive adequate instruction on these requirements commensurate with their responsibilities.

Section 15 - Regulatory Information

Special requirement be according to the local regulations.

《Dangerous Goods Regulations》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous goods 》

《Occupational Safety and Health Act 》 (OSHA)

《Toxic Substance Control Act》 (TSCA)

《Consumer Product Safety Act 》 (CPSA)

《Federal Environmental Pollution Control Act》 (FEPCA)

《The Oil Pollution Act》 (OPA)

《Superfund Amendments and Reauthorization Act TitleIII(302/311/312/313) 》 (SARA)

《Resource Conservation and Recovery Act》 (RCRA)

《Safety Drinking Water Act》 (CWA)

《California Proposition 65》

《Code of Federal Regulations》 (CFR)

Section 16 - Other Information

| | |
|-------------|---|
| Note | This Sheet is provided as technical information only. The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. DongGuan Precise Testing and Certification Corp. Ltd. (PTC), makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it. |
|-------------|---|

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission

DongGuan Precise Testing and Certification Corp. Ltd. (PTC)

Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.

Tel: 86-769-38808222

Fax: 86-769-38826111

[http:// www.ptc-testing.com](http://www.ptc-testing.com)



MSDS

Report No.: PTC19081602503C-EN01

Issue Date: Nov. 05, 2019

Page 8 of 8

Photo(s) of Sample:



End of MSDS

This report is issued according to the general clauses in www.ptc-testing.com by PTC. Responsibility, guarantee and law restriction are defined in the general service clauses. The report is only responsible for the submitted sample(s) except as otherwise noted.

The report could not be copied without permission

DongGuan Precise Testing and Certification Corp. Ltd. (PTC)
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.
Tel: 86-769-38808222 Fax: 86-769-38826111 [http:// www.ptc-testing.com](http://www.ptc-testing.com)